

Bypass Valve Kits



AVK Bypass Kit

Reduce the potential for valve seat damage from filling the pipeline too quickly.

Bypass valve may be Non-Rising Stem or OS&Y.

Equalize pressure for opening the large gate valve, insuring longer valve life.

Fully compliant with AWWA requirements for bypass valves
18-inch — 3-inch
20-inch — 3-inch
24-inch — 4-inch

Zinc plated or 304 stainless steel bolting is available

No need to throttle the gate valve when filling a pipeline; ensures longer valve life ... protecting your investment.

Bypass valve is MJ x MJ for easy installation

- Save time and money over building up bypass assemblies in the field
- Bypass can be delivered as a complete pressure tested assembly ready for installation, or can delivered as a kit ready for assembly in the field.
- All required hardware is included for field assembly.
- The bypass kit will fit all manufacturers FL x FL gate valves.
- The available bypass kit end configurations are:
 - MJ x MJ
 - FL x FL
 - MJ x FL

The AVK bypass kit includes (shown in rust color):

- Two spool pieces
- Two elbows
- One MJ x MJ bypass valve
- All necessary bolting to assemble the kit
- Bolting to install valve and bypass assembly into the pipeline is not included

American AVK Company Locations To Serve You:

Minden, NV
Tel: (775) 552-1410
Fax: (775) 783-7502

N. Charleston, SC
Tel: (843) 552-5557
Fax: (843) 552-8852

Dallas, TX
Tel: (775) 552-1410
Fax: (775) 783-7502


AMERICAN AVK COMPANY
www.americanavk.com