

EXPECT
RELIABILITY




AVK SERIES 145 VALVES RESILIENT WEDGE VALVE DESIGNED FOR VALUE

AVK STANDARD FEATURES

- Series 145 Gate Valves are made of ductile iron with a 250 PSI rated working pressure, in sizes 2½"-8"
- Comes standard with 1 boss hole, drilled, tapped and plugged
- Available in both NRS and OS&Y configurations
- ASTM A276 stainless steel stems
- Cold-rolled threading process eliminates bent or broken stems
- Electrostatically applied, fusion bonded epoxy resin provides extended corrosion resistance
- Bonnet bolts are fully isolated against corrosion to eliminate bonnet bolt failures
- All AVK Series 145 Gate Valves are covered by a 2 year warranty
- UL/ULC listed and FM approved
- Made in the USA

FULLY ENCAPSULATED EPDM WEDGE DUCTILE IRON CORE

- Patent pending "Slim Wedge" design with integral wedge shoes reduces operating torque
- Fully encapsulated EPDM wedge prevents deterioration from disinfectants
- Fixed wedge-nut provides higher torque resistance and prevents rubber wear and leakage



WHEN EVERY SECOND COUNTS COUNT ON AVK

AVK SERIES 34 WALL POST INDICATORS


- Available in three fixed lengths
- Handwheel can be locked to prevent tampering
- Pre-cast, threaded boss is provided for supervisory switch mounting
- 1 year limited warranty
- UL/ULC listed and FM approved



UL/ULC LISTED FM APPROVED

AVK FIRE PROTECTION SERIES 45 VALVES


- Full wall, ductile iron bodies with stainless steel stems
- Available in Flange x Flange, Mechanical Joint x Flange, and Mechanical Joint x Mechanical Joint end configurations, with post indicator plates for AVK Series 34 Telescoping Indicator Posts
- Grooved x Grooved and Grooved x Flanged end configurations in both NRS and OS&Y models
- 250 PSI rated working pressure
- 2 year limited warranty
- UL/ULC listed and FM approved



SERIES 34 - UL/FM TELESCOPIC POST INDICATORS

AVK SERIES 34 TELESCOPIC POST INDICATORS

- Available for valve sizes 2½" through 24"
- UL approved for valve sizes 4" through 24"
- FM approved for valve sizes 4" through 24"
- PVC Lower Barrel standard
- Optional ductile iron Lower Barrel
- Electrostatically applied, fusion bonded epoxy resin provides extended corrosion resistance
- 1 year limited warranty
- Made in the USA





American AVK Company Locations

American AVK Company

2155 Meridian Blvd.
Minden, NV
89423
USA

Tel.: 775-552-1400
Fax.: 775-552-1031
sales@avkus.com
www.americanavk.com

F99007/11-05-2024
Copyright©AVK Group A/S 2024

