

SERIES 67, POST/FLUSHING, DRY BARREL HYDRANT – OPTIONS

SERIES 67, POST/FLUSHING, DRY BARREL HYDRANT OPTIONS

• Hose Nozzle

☐ Thread type _____

• Chains

☐ With Chains
☐ Without Chains

• Operating Nut

☐ Size _____
☐ Shape _____
☐ Handwheel Mounted on Weathershield
☐ Handwheel Mounted on Weathershield- w/ extra drain holes

• Bolting Above Ground

☐ Zinc Plated (standard)
☐ 304 Stainless Steel
☐ 316 Stainless Steel

• Bolting Below Ground

• 316 Stainless (Standard)

• Opening Direction

☐ Open Left
☐ Open Right

• Drain Facility

☐ Unplugged (Standard)
☐ Plugged

• Upper Stem

• 304 Stainless (Standard)

• Lower Stem

☐ 108 Steel (Standard)
☐ 304 Stainless Steel

• Inlet Configurations

☐ MJ 2" ☐ 3" ☐ 4" ☐
☐ NPT 2" ☐ 2.5" ☐ 3" ☐
☐ FL 2.5" ☐ 3" ☐
☐ Hymax 2" ☐

• Bury Depth, Lower Barrel

☐ Depth in feet (In 6" increments) _____

• Color

☐ Body _____
☐ Hose Cap _____
☐ Base _____
☐ Lower Barrel(s) _____
☐ Weathershield _____
☐ Special Color _____

• Special Options – All special options must be approved by AVK

Customer: _____

Municipality: _____

Engineer: _____

Requested By: _____

Date: _____

Approver Name: _____

Signature: _____

Title: _____